





Radiator Unit Part No. PDC-90SR									
Installation Environment	Outdoor								
IP Rate*1	IP55								
Color	Light Beige								
Input Power Unit	90W Midspan								
Operating Temperature	−20~+50°C								
Operating Humidity	below 95%RH								
Thermostat	nermostat Cool+25~+45°C(variable)Heat 0°C~10°C(variable)programmable								
Warning Monitor	Temperature in Housing, Temperature of Radiator Unit, Flow of Antifreeze								

Part Number	Cooling Power(W)	Heating Power(W)	Dimension (mm)		(mm)	Rated Power		Noise	Weight
	*1,	*2	W	Н	D	PoE *2	12VDC	dB(A)	kg
Radiator Unit PDC-90SR	- 60	50	300	400	187	90WMidspan (2pcs)	12V/7.5A 90W	TBD	TBD
Cooling Unit in Housing PDC-90SU			138	67	150	Microsemi Compatible		TBD	TBD

- *1. Rated by Midspan 2 pcs., Setting Cooling Temperature35°C、Heating Temperature 5°C.
- *2. Rated Cooling Power 40W, Heating Power 35W by Midspan 1 pc.
- *3. Height between Housing and Radiator shall be within 2m.
- *4. Additional Heater is recommended for extreme cold area.

Optional Accessories

Sunshade Box for Radiator Unit (Material SUS304)

*For Protection of Radiator Unit from Sunlight

A-SSBX400





Pole Mount Adaptor(Material SUS304)

*1 pc each necessary for both Housing and Sunshade Box

A-BK6S(OW) Off-white A-BK6S(DB) Dark Brown

A-BK6S Black



Anti-Strong Wind Bracket for Housing (Material SUS304)

A-BRK20



Note: This Right Angle Bracket is A-BRK20.

Wall Mount Bracket for Housing (Material SUS304)

A-WMB102



Front Direction Adjustable Bracket (Material SUS304)

A-PAN90

*Adjustable PanLeft 45°Right 45° Useful for Beveled Dome Housing



% Specifications are subject to change without prior notice

http://www.kk-asc.com



ASC Corporation

3-16-9, Toranomon, Minato-ku, Tokyo 105-0001, Japan Tel: +81-3-5473-7627 Fax: +81-3-5473-7628

(Wholesale for U.S.A Market only)

ASC-USA, INC.

Tel: 770-888-4674 / 1-888-988-4674 Fax: 770-888-4675

5975 Shiloh Road, Suite 103, Alpharetta, GA 30005